

18" Washdown Urinal

FXR-SS-U-2020 Series



Fixture maybe featured with available options.

Specification Guide

- Wall hung urinal with optional top or back supply.
- Back supply flushing connection $\frac{3}{4}$ " MIPT.
- Top supply flushing connection $\frac{3}{4}$ " MIPT.
- Washdown flushing action.
- $1\frac{1}{2}$ " OD P-trap for slip-joint connection.
- Vandal resistant stainless steel trap enclosure.
- High volume beehive style strainer.
- Furnished with necessary fasteners for proper installation.

Note: Optional Wall Sleeve or Metal Template is recommended for all installations with required wall openings.

► Description

This Washdown Urinal is designed for high security areas with an accessible pipe chase. Fixtures are fabricated using 14-gauge type 304 stainless steel seamlessly welded to form a one piece, tamper resistant fixture. Flushing provides a sanitary wash-down of the interior. Exposed surfaces are polished to a satin finish. Fixtures come with a beehive type strainer, P-trap and vandal resistant stainless steel trap enclosure.

► Recommended I-CON Intelligent Control System

The system includes low voltage water resistant controllers, waterproof stainless steel actuators, direct acting solenoid valves with no diaphragms, and an ASSE certified flush valve proven to be more reliable and less expensive to maintain than traditional valves. The I-CON System can be configured as a standalone or communicating system linked to our touchscreen PC technology, which both configurations offer with the capability to stop flooding and abuse while managing toilet flushes per hour/per fixture reducing water usage and sewer costs.



► Accessories & Options

See accessories and available options on page 2.

